

DIALOG(R)File 351:DERWENT WPI
(c)1997 Derwent Info Ltd. All rts. reserv.

010453876

WPI Acc No: 95-355195/199546

Agent ***masking*** ***unpleasant*** ***taste*** of medicine - comprises unpleasant tasting medicine, hydrophobic agent, surfactant and water transporting agent

Patent Assignee: EISAI CO LTD (EISA)

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Main IPC	Week
JP 7242568	A	19950919	JP 9458272	A	19940304	A61K-047/44	199546 B

Priority Applications (No Type Date): JP 9458272 A 19940304

Patent Details:

Patent	Kind	Lan	Pg	Filing	Notes	Application	Patent
JP 7242568	A		4				

Abstract (Basic): JP 7242568 A

Compsns. composed of (1) an unpleasant tasting medicine, (2) a hydrophobic agent having m.pt. 45-90 deg. C, (3) a surfactant, and (4) a water transporting agent, and their spray-dried particle prepns. are used for pharmaceutical prepns.

Cpds. (1) are mixed with a hydrophobic agent (2) (e.g, was, ***fat***, higher fatty acid triglycerides, higher fatty acid and higher alcohols), (3) a surfactant (e.g, esters of higher ***fatty*** acids, polyoxyethylene ***hydrogenated*** castor ***oil*** and Na laurylsulphate) and cpds.), (4) a water transporting agent of water soluble or dispersible cpds. (e.g, hydroxypropylcellulose, CMC and partial alpha-starch) at ratios of (1):(2):(3):(4) = 1-50:25-90:5-35:5-35%, pref. 1-40:40-80:10-30:10-30%, more pref. 1-30:50-80:10-30:10-20%, respectively. The resultant compsn. are spray dried to give particles for granular, particle, powder and dry syrup prepns.

USE/ADVANTAGE - Pharmaceutical prepns. without unpleasant taste. Oral medicines can be administered smoothly.

In an example, a mixt. of 15 pts. wt. of ***hydrogenated*** castor ***oil*** and 10 pts. wt. of a sugar ester was melted on a water bath and 10 pts. wt. of ticlopidine HCl and 5 pts. wt. of hydroxypropyl cellulose were homogeneously dispersed. The dispersed mixt. was spray dried to give a particle prepn.

Dwg.0/0

Derwent Class: A96; B05

International Patent Class (Main): A61K-047/44

International Patent Class (Additional): A61K-009/14